

Basic Cleaner BETA

Basic cleaner



Area of application: For removing of aged wax and polymer films and persistent dirt residues.
For the basic cleaning of all water- and alkaline-resistant floorings.
Especially suitable for removing metal-reinforced films.

- Properties:**
- Power-increased
 - It effectively removes aged coatings of wax and plastic dispersions
 - Foam-inhibited

Technical data:

Nature of the product	Liquid
Colour	Slightly yellowish
pH-value (concentrate)	approx. 13 - 14
pH-value (10 %)	approx. 11

Application:

Application	Dilution
Depending on age and thickness of the film:	1 : 5 to 1 : 10
Homogeneously distribute the solution and allow it to act for 5 to 15 minutes. Then, scrub the floor with a scrubber or a cleaning machine and the appropriate pad. Pick up released dirt and re-wipe with plenty of water.	
Caution: Risk of slipping!	
If the surface shall be coated then with PUDOL Opal Sealant , especially make sure that the floor will be neutralise thoroughly. If necessary, add some PUDOL Rapid Cleaner in the last mopping water.	
Process wide areas step by step.	

Storage:

Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures.
In closed original trading units at room temperature it is stable for at least 24 months.

Packaging unit:

1 l bottle, 12 pieces in cardboard box	Art.No.: 2700 - 00100
10 l canister, 60 canisters per pallet	Art.No.: 2700 - 01000
Other trading units on request.	

Special information:

For commercial use only.
The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.
Please, also consider the Safety Data Sheet!