


Dekrustan

Intensive degreaser



Range of application: For removing of massive dirt deposits as well as burned-in oil and fat films. It is applicable on all washable materials like stainless steel, chromium, brass, silver, plastics, ceramics, concrete. It is also recommended for removing of resin on forest and wood-processing machines.

- Properties:**
- Intensive cleaning effect
 - It penetrates even thick dirt layers and removes them reliably
 - If foamed up with suitable devices (e. g. foam lance) the diluted solution forms a stable and actively cleaning foam padding
 - Free from phosphate

Technical data:

| | |
|-------------------------------|--------------------|
| Nature of the product | Liquid |
| Colour | Slightly yellowish |
| pH-value (concentrate) | approx. 14 |
| pH-value (1 %) | approx. 12.5 |

Application:

The cleaner can be applied in spraying and wiping procedures in immersion parts washers and can be foamed up. In the field of canteen kitchens, heat up the devices to +60°C beforehand. Apply the solution, allow it to act for 5 to 10 min. and rinse it. If necessary, use a hard sponge. Select the dosing value depending on the degree of pollution. Extremely encrusted oil and fat deposits (of mineral, animal, or plant origin) require a longer duration of exposure depending on their thickness. Longer application time and hot water improve the effect.

| Application | Dilution |
|---|-------------------|
| Basic cleaning, removing of encrustations: | 1 : 5 to 1 : 10 |
| Baking plants, baking sheets, cake moulds, roasting dishes, pans: | 1 : 10 to 1 : 30 |
| Vents. filters, grills, ventilation shafts: | 1 : 20 to 1 : 40 |
| Disposal shafts, channels, concrete and clinker floors in workshops and in the meat industry: | 1 : 30 to 1 : 100 |
| Application in high-pressure cleaners, steam jets: | |
| a) pre-diluted: | 1 : 5 to 1 : 10 |
| b) directly fed: | 1 : 90 to 1 : 100 |

Storage:

Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures. In closed original trading units at room temperature it is stable for at least 24 months.

Dekrustan

Intensive degreaser



Packaging unit: 1 l bottle, 12 pieces in cardboard box Art.No.: 6756 - 00100
10 l canister, 60 canisters per pallet Art.No.: 6756 - 01000
Other trading units on request.

Special information: For commercial use only.
The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.
Please, also consider the Safety Data Sheet!