

## Oil Binder MULTISORB Type III R

### Multipurpose binder



#### Area of application:

For binding of oil, fat, chemicals (pre-test) and other liquids.

For absorbing and gritting of escaped oils and liquids in the road traffic, on airports, in workshops, industrial companies and refineries.

For occupational safety; it prevents personal injuries, damages to environment and property - suitable for oils and chemicals.

#### Properties:

- Calcinated alumina
- Especially high and fast absorbing capacity
- Easy handling
- Good flowing and gritting ability
- Low-dust
- High anti-skid property
- Harmless for human and animal
- Free from hazardous substances known
- Non-toxic
- Not caustic
- Non-flammable (bound oil can be burned off)

#### Technical data:

<b>Nature of the product</b>	Granulate
<b>Colour</b>	Light beige
<b>Granulate size</b>	0.5 - 3.2 mm
<b>Bulk weight</b>	640 g/l
<b>1 kg binds approx.</b>	0.7 l heating oil

#### Application:

After spreading on, allow it to act for some minutes.

#### Storage:

Always keep containers well closed, out of sunlight and out of reach of children. Do not expose to high temperatures.

In closed original trading units at room temperature it is stable for at least 24 months.

#### Packaging unit:

20 kg bag, 55 pieces per pallet

Art.No.: 8390 - 02000

Other trading units on request.

#### Special information:

Please, always observe the details in the safety data sheet of the substance to be absorbed!

For commercial use only.

The characteristics mentioned here are not binding. We reserve the right to make certain changes due to product improvements or necessary raw material replacement. Users are responsible for checking the suitability of the products for use on materials not mentioned. Our advice is therefore non-binding and cannot be used as a basis for liability claims against us.

*Please, also consider the Safety Data Sheet!*